



## Outdoor Enclosure / PSOD Series



**PSOD-302420**

30"H X 24"W X 20"D

**PSOD-302420FT**

30"H X 24"W X 20"D

### Features

#### Standard Model

- Two RF cover plates over .065" dia. hole (for type N RF con) on back of unit
- One Power cover plate with 3/4" dia. hole on back of unit
- Louvered 5" x 5" 5 micron nylon filter / Removable Side Panel
- (2) 4" C-Channel with slots for mounting on rear

	<ul style="list-style-type: none"> <li>1 Set Standard EIA Rails</li> </ul>
<b>FT Model</b>	<ul style="list-style-type: none"> <li>Cooling Fan (F-25-115T) Dual Fan 220 cfm Adjustable Thermostat</li> <li>2 Populated Duplex Electrical gangboxes with 4 outlets total</li> <li>Two RF knockouts .065" dia. (for type N RF con) on back of unit</li> <li>One Power knockouts 3/4" dia. on back of unit</li> <li>Louvered 5" x 5" 5 micron nylon filter / Removable Side Panel</li> <li>(2) 4" C-Channel with slots for mounting on rear</li> <li>1 Set Standard EIA Rails</li> </ul>

## Specifications

### General

<b>Weight</b>	70 lbs
<b>Door</b>	Single Door sealed by Gasket filled rubber
<b>Material</b>	0.125" Alumiflex (non-corrosive) Powder-Coat Paint 3 step tiger drylac
<b>Rails</b>	Inset 1 1/2" from door with 1" adjustability. Can be reversed for deeper inset ability.
<b>Handles</b>	Pad Locking Handle

### Mounting

<b>C-Channel Feet</b>	Width: 4 inches Height: 2 inches Length: 23 1/2inches
<b>Mounting Slots</b>	Width: 1/4 inch Height: 1 inch
<b>Spacing</b>	2 inch on center, 3/4 inch from end to center first slot

### Exterior Cabinet Dimensions

<b>Main Body</b>	Width: 24 inches Height: 31 inches Depth: 20 inches
<b>Door Opening</b>	Width: 21 1/2 inches Height: 28 inches
<b>Total Space Occupied</b>	Width: 24 inches Height: 31 inches Depth: 26 3/4inches

### Inside Clearance - Less Rails

<b>Width</b>	23 1/2 inches
<b>Height</b>	31 inches
<b>Depth</b>	18 inches

### Warranty

<b>Period</b>	15 Years - Unconditional
---------------	--------------------------