

IOD-46DXC

46" H x 25" W x 30" D (23 RU) Indoor/Outdoor Enclosure



General

Weight

- 121 Lbs. assembled
- 191 Lbs. shipping weight

Doors

- 2, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- One removable filter panel per door

Handles

- Zinc, padlocking

Racking Specifications

Rails

- Four standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex®)

Spacing

- 19" or 23" Racking available

Useable Height

- 46"

Useable Depth

- Maximum: 26.375" Minimum: 25.75"

Removable Front Door

Opening Clearance

- Height: 42.25"
- Width: 19.5"

Removable Back Door

Opening Clearance

- Height: 37.375"
- Width: 19.5"

Inside Clearance - Less Rails

Height

- 46"

Width

- 23.625"

Depth

- See racking specifications
– Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 42.25"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 46.25"
- Width: 25.5"
- Depth: 30"

Handles

- Protrude 2.2"

Total Space Occupied

- Height: 46.375"
- Width: 25.625"
- Depth: 34"