

# OD-62DDC

## 62" H x 25" W x 34" D (33 RU\*) Outdoor Enclosure



### General

#### Weight

- 177 Lbs. assembled
- 247 Lbs. shipping weight

#### Doors

- 2, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

#### Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

#### Vents

- 30 bottom louvers per door
- 14 top louvers – In top cover, under Alumishield®
- One removable filter panel per door
- 14 fixed filter pads in top cover

#### Handles

- Zinc, padlocking

### Racking Specifications

#### Rails

- Two sets 19" Rails standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex®)

#### Spacing

- 19" or 23" Racking available

#### Useable Height

- Usable racking height has been revised to only fit in the opening of the door jam which is cabinet height minus 4.25"
- Maximum: 58.25"
- Number of rack units per rail set: 33
- Total number RU's: Up to 66\*

#### Useable Depth

- Maximum: 30.5" Minimum: 28.75"

### Inside Clearance - Less Rails

#### Height

- 62.23"

#### Width

- 23.625"

#### Depth

- See racking specifications – Useable depth

### Ratings

#### NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

#### Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

### Door Opening Clearance

#### Height

- 58.25"

#### Width

- 19.5"

### Exterior Cabinet Dimensions

#### Main Body

- Height: 62.48"
- Width: 25.5"
- Depth: 34"

#### Alumishield®

- Width: 28.46"
- Hang down height: 1.71"
- Depth: 36.67"

#### Handles

- Protrude 2.2"

#### Total Space Occupied

- Width: 28.46"
- Height: 63.1v05"
- Depth: 37.75"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	58.75" – 62.48"	3.25"	30.50"
	58.57" – 58.75"	.18"	29.50"
	37.00" – 58.57"	21.57	30.50"
Center	25.00" – 37.00"	12.00"	28.75"
	3.43" – 25.00"	21.57	30.50"
	3.25" – 3.43"	.18"	29.50"
Bottom	0.00" – 3.25"	3.25"	30.50"

\* Front and Rear sets of rails allow some equipment to rack both directions providing up to 66 RU