

OPSOD-102420FT

10" H x 24" W x 20" D (5 RU) Outdoor Enclosure



General

Weight

- 40 Lbs. assembled

Doors

- Single door sealed by Gasket filled rubber

Material

- .125" Alumiflex™ (non-corrosive)
- Finish: Painted cream

Handles

- Quarter turn padlocking handle

Racking Specifications

Rails

- One set standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- .125" Material (Alumiflex™)

Spacing

- 19" EIA standard

Useable Height

- Height: 10"

Useable Depth

- Maximum: 21.5" Minimum: 19.75"

Mounting

C-Channel Feet

- Width: 4"
- Height: 2"
- Depth: 3.5"

Mounting Slots

- Width: .125"
- Height: 1"

Spacing

- 2 inch on center, .75" inch from end to center first slot

Inside Clearance - Less Rails

Height

- 9.75"

Width

- 23.75"

Depth

- 19.75"

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 8"

Width

- 21.5"

Exterior Cabinet Dimensions

Main Body

- Height: 10"
- Width: 24"
- Depth: 20"

Total Space Occupied

- Height: 11"
- Width: 24"
- Depth: 26.625"