

# PNOD-102420FT

## 10" H x 24" W x 20" D (5 RU) Outdoor Enclosure



### General

#### Weight

- 40 Lbs. assembled

#### Doors

- Single Door sealed by Gasket filled rubber

#### Material

- .125" Alumiflex™ (non-corrosive)
- Finish: Painted cream

#### Handles

- Quarter turn padlocking handle

### Mounting

#### C-Channel Feet

- Width: 4"
- Height: 2"
- Depth: 19"

#### Mounting Slots

- Width: .125"
- Height: 1"

#### Spacing

- 2 inch on center, .75" inch from end to center first slot

### Racking Specifications

#### Rails

- One set standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- .125" Material (Alumiflex™)

#### Spacing

- 19" EIA standard

#### Useable Height

- Height: 10"
- 5 RU

#### Useable Depth

- Maximum: 21.5" Minimum: 19.75"

### Inside Clearance - Less Rails

#### Height

- 9.75" (Horizontal Width)

#### Width

- 23.625" (19" EIA Racking)

#### Depth

- 18" (Vertical Height)

### Exterior Cabinet Dimensions

#### Main Body

- Height: 10" (Horizontal Width)
- Width: 24"
- Depth: 21" (Vertical Height)

#### Total Space Occupied

- Height: 14" (Horizontal Width)
- Width: 24"
- Depth: 21" (Vertical Height)