

SOD-372420-VB1

37" H x 24" W x 20" D (16 RU) Wimax Enclosure



General

Weight

- 410 Lbs. assembled
- 470 Lbs. shipping weight

Doors

- Louvered 7.5" x 10"
- 5 micron nylon filter
- Gasket filled rubber

Material

- .125" Alumiflex™ (non-corrosive)
- Finish: Painted cream

Handles

- Quarter turn padlocking handle

Racking Specifications

Rails

- One set standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- .125" Material (Alumiflex™)

Spacing

- 19" EIA standard

Useable Height

- Height: 37"

Useable Depth

- Maximum: 21.5" Minimum: 19.75"

Inside Clearance - Less Rails

Height

- 36.75"

Width

- 23.75"

Depth

- 19.75"

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Exterior Cabinet Dimensions

Main Body

- Height: 37"
- Width: 24"
- Depth: 20"

Total Space Occupied

- Height: 38"
- Width: 24"
- Depth: 22.5"

Comes with:

- 2400 BTU Air Conditioner 110 Volts
- (4) 100 Amp Battery
- Battery Tray
- 60 Amp Main Load Center w/ 2 Populated 4 Square Outlets
- .5 Insulation