

## Indoor/Outdoor Cabinet 46"H X 30"D

**IOD-46DXC**

46"H X 30 1/2"D X 25 3/4"W (19" Racking) **Painted Cream** 220 CFM  
115 Volt Fan Kit with Adjustable Thermostat

Standard 2 Sets of 19" Rails





### FEATURES

**HANDLES** - Stainless steel - NEMA

**RAILS** - Fully adjustable & alodine coated

**DOORS** - Removable Front and rear secured with three point locks and padlocking handles

**VENTS** - Front & Rear Doors, Filters Supplied

The **IOD-46DXC** is the superior design in communication cabinets, being as rigid as steel & yet noticeably lighter than the old heavy steel constructed cabinets. This is made possible with our own aluminum recipe called ALUMIFLEX. The **IOD-46DXC** offers the protection needed for any severe outdoor environment. The **IOD-46DXC** is constructed of .125 ALUMIFLEX material. Ultimate security is provided by a three point locking system, which utilizes a NEMA stainless steel padlocking handle. Unlike steel cabinets, the **IOD-46DXC**, made of ALUMIFLEX, will operate without affecting or being effected by RF influences. Outdoor cabinets are becoming the alternative shelter solution for today's complicated zoning requirements. So whether your installing a new shelter or adding room to your existing one, the **IOD-46DXC** is the ultimate solution.

### GENERAL

<b>Weights:</b>	132 Lbs. Assembled 180 Lbs. Shipping weight
<b>Doors Removable:</b>	Two - secured by three point locking system Locks via customer supplied padlocks Sealed with 13/16" aluminum filled gaskets
<b>Materials:</b>	.125 ALUMIFLEX Finish: Flat aluminum RF properties: Non-ferrous
<b>Vents:</b>	30 Filtered Louvers per door One removable filter panel per door
<b>Fan Kit Assemble</b>	1 - 110 CFM 115 Volt Fan per Door with Adjustable Thermostat
<b>Handles:</b>	Stainless steel
<b>Exterior Screws:</b>	Stainless with NEMA washers & nylon locking nuts

**RACKING SPECIFICATIONS**

<b>Rails:</b>	Four standard (For additional rails see accessories) Holes tapped to 10 x 32 threads Each rail supported by three R-STRUTS .125 material (ALUMIFLEX)
<b>Spacing:</b>	19" EIA STANDARD
<b>Positioning:</b>	All rails fully adjustable from front to rear
<b>Useable Height:</b>	46 inches
<b>Useable Depth:</b>	Maximum: 26 3/8    Minimum 25 3/4

**REMOVABLE FRONT DOOR OPENING CLEARANCE**

<b>Width:</b>	19 1/2 inches
<b>Height:</b>	41 3/4 inches

**REMOVABLE BACK DOOR OPENING CLEARANCE**

<b>Width:</b>	19 1/2 inches
<b>Height:</b>	36 3/4 inches

**EXTERIOR CABINET DIMENSIONS**

<b>Main Body:</b>	Width: 25 1/2 inches Height: 46 1/2 inches Depth: 30 inches
<b>Handles:</b>	Protrude 1 7/8 inches

**INSIDE CLEARANCE - LESS RAILS**

<b>Width:</b>	23 5/8 inches
<b>Height:</b>	46 inches
<b>Depth:</b>	See racking spec's - useable depth chart above

**RATINGS**

<b>NEMA:</b>	CLASS: 250 TYPE: 4
--------------	-----------------------

**WARRANTY**

<b>PERIOD:</b>	<b>SEVEN YEARS - UNCONDITIONAL</b>
----------------	------------------------------------

***ACCESSORIES******ACCESSORIES & CLIMATE CONTROL OPTIONS***

<b>R-2-46:</b>	Two extra 46" rails & mtg. hardware
<b>MTDX:</b>	Mounting tray
<b>CA-4:</b>	Caster Kit (4) & mtg. hardware

**SHIPPING INFORMATION**

The **IOD-46DXC** is shipped fully assembled, but can be easily knocked down and re-assembled at your site, if desired.