

## Outdoor Cabinet 60"H X 42"D

**OD-62DDX**
*62"H X 42"D X 25"W (19" or 23" Racking)*
**OD-62DDXC**
*62"H X 42"D X 25"W (19" or 23" Racking) **Painted Cream***

*Standard 2 Sets of 19" Rails*

OD-62DDX



OD-62DDXC



**OD-62DDX (C) = ENCLOSURE PAINTED CREAM**

### FEATURES

**ALUMISHIELD:** Top cover, shades cabinet from the sun

**HANDLES:** Stainless steel - NEMA

**RAILS:** Fully adjustable & alodine coated

**DOORS:** Front and rear secured with three point locks and padlocking handles

**VENTS:** Front & rear, top & bottom, filters supplied

The OD-62DDX is the superior design in communication cabinets, being as rigid as steel & yet noticeably lighter than the old heavy steel constructed cabinets. This is made possible with our own aluminum recipe called ALUMIFLEX. The OD-62DDX offers the protection needed for any severe outdoor environment. The OD-62DDX is constructed of .125 ALUMIFLEX material, & comes with an additional .125 ALUMISHIELD top cover, thereby fully protecting your equipment from falling ice and the sun's heat penetration. Ultimate security is provided by a three point locking system, which utilizes a NEMA stainless steel padlocking handle. The OD-62DDX, made of ALUMIFLEX, will operate without affecting, or being effected by, RF influences. Outdoor cabinets are becoming the alternative shelter solution for today's complicated zoning requirements. So whether your installing a new shelter or adding room to your existing one, the OD-62DDX is the ultimate solution.

**SPECIFICATIONS****GENERAL**

*Weight:* 210 lbs. assembled  
255 lbs. Shipping weight

*Doors:* two - secured by three point locking system  
Locks via customer supplied padlocks  
sealed with 13/16" aluminum filled gaskets

*Material:* .125 ALUMIFLEX  
*Finish:* Flat aluminum  
*RF properties:* Nonferrous

*Vents:* 30 bottom louvers per door  
Six top louvers - In top cover-under ALUMISHIELD  
One removable filter panel per door  
Six fixed filter pads in top cover

*Handles:* Stainless steel

*Exterior Screws:* Stainless with NEMA washers & nylon locking nuts

**RACKING SPECIFICATIONS**

*Rails:* Two standard (For additional rails see accessories)  
Alodine coated  
Holes tapped to 10 x 32 threads  
Each rail supported by three R-STRUTS  
.125 Material (ALUMIFLEX)

*Spacing:* 19" EIA STANDARD

*Positioning:* All rails fully adjustable from front to rear

*Useable Height:* 62 inches

*Useable Depth:*  
Maximum: 38 1/2" Minimum 36 3/4" (See below)

	*Section Starting & Ending Points	Vertical Height Per Section	Effective Depth For each section
<u>Top</u>	58.75" - 62.00"	3.25"	38 1/2"
	58.57" - 58.75"	.18"	37 1/2"
	37.00" - 58.57"	21.57"	38 1/2"
<u>Center</u>	25.00" - 37.00"	12.00"	36 3/4"
	3.43" - 25.00"	21.57"	38 1/2"
	3.25" - 3.43"	.18"	37 1/2"
<u>Bottom</u>	0.00" - 3.25"	3.25"	38 1/2"

**\*Section measurements start from the bottom of the cabinet (0.00") & run vertically upward towards the top of the cabinet (62.00"):**

**DOOR OPENING CLEARANCE**

<i>Width</i> : 19 1/2 inches
------------------------------

<i>Height</i> : 57 13/16 inches
---------------------------------

<b>EXTERIOR CABINET DIMENSIONS</b>
------------------------------------

<i>Main Body</i> ::
---------------------

Width: 25 1/2 inches
----------------------

Height: 62 1/4 inches
-----------------------

Depth: 42 1/4 inches
----------------------

<i>ALUMISHIELD</i> :
----------------------

Width 28 1/16 inches
----------------------

Hang down height: 1 3/4 inches
--------------------------------

Depth: 44 11/16 inches
------------------------

<i>Handles</i> : Protrude 1 7/8 inches
--

<i>Total Space Occupied</i> :
-------------------------------

Width: 28 1/16 inches
-----------------------

Height: 62 1/2 inches
-----------------------

Depth: 46 inches
------------------

<b>INSIDE CLEARANCE - LESS RAILS</b>
--------------------------------------

<i>Width</i> : 23 5/8 inches
------------------------------

<i>Height</i> : 62 inches
---------------------------

<i>Depth</i> : See racking Spec's - useable depth chart above
---

<b>RATINGS</b>
----------------

<i>NEMA</i> : CLASS: 250
--------------------------

<i>TYPE</i> : 4
-----------------

<i>Paint Tested</i> :
-----------------------

500 Hour salt spray
---------------------

500 hour immersion
--------------------

<b>WARRANTY</b>
-----------------

<b>PERIOD: SEVEN YEARS - UNCONDITIONAL</b>
--

<b><i>ACCESSORIES</i></b>
---------------------------

<b><u><i>ACCESSORIES &amp; CLIMATE CONTROL OPTIONS</i></u></b>
--

<i>R-2-62</i> :
-----------------

Two extra 62" rails & mtg. hdw.
---------------------------------

<i>MTDX</i> :
---------------

Mounting tray
---------------

<i>CA-4</i> :
---------------

Caster kit (4) & mtg. hdw.
----------------------------

<b>SHIPPING INFORMATION</b>
-----------------------------

The OD-62DDX is shipped fully assembled, but can easily be knocked down and reassembled at your site, if desired.
---