

Outdoor Cabinet 37"H X 24"W X 20"D

SOD-372420-LAC

<i>37"H X 24"W X 20"D w/ standard 19" EIA Racking</i>
<i>2000 BTU AIR CONDITIONER 110V W/Insulation</i>
<i>60 AMP Load Center w/ 2 - 4 Square Outlet Boxes</i>
<i>Fluorescent Light Installed</i>
<i>Optional = (HT-100) 100 W Heater</i>





SOD-372420-LAC

37" OUTDOOR WIRELESS ENCLOSURE

LIGHTWEIGHT ALUMINUM

35" X 22" X 18" USABLE SPACE

Physical

Exterior Dimensions 37"H x 24"W x 20"D + AIR CONDITIONER AND LOAD CENTER

Interior Dimensions 35"H x 22"W x 18"D

Weight 130 Lbs (Cabinet w/ Load Center and Air Conditioner)

<u>AC-2000I</u>	2000	120/60	5.2	125F	60lbs	22.25"H x 11.5"W x 6.25"D
<u>AC-2000I2</u>	2000	230/60	2.6	125F	60lbs	22.25"H x 11.5"W x 6.25"D

Construction

Material 0.125" Alumiflex (non-corrosive)

Powder-Coat Paint 3 step tiger drylac

Door

Louvered 7.5 " x 10" 5 micron nylon filter

Pad Locking Handle

Gasket filled rubber

Equipment Mounting

EIA Std 19" Racking Rails -- 18U (31.5") of rack space

Environmental Options

Air Cond. (AC-2000I) 2000 BTU A/C 110 or 220 Volts AC

Heating (HT-100) 100 watt with tempstat (on 45deg, off 55)

Features Standard

2000 BTU AIR CONDITIONER 110V (220V UPON REQUEST)

1/2" Insulation Installed (.5INS)

60 Amp Main Electrical with 2 Populated 110V 4 Square Outlets (each 4-SQ is on its own 20 Amp Breaker)

Fluorescent Light Installed

Four RF knockouts .065" dia. (for type N RF con) on floor of unit

Four Power knockouts 3/4" dia. on floor of unit

Ground stud on floor of unit

Warranty 7 years