

30D-30DXC

30" H x 88.5" W x 25" D (45 RU) Outdoor Enclosure



General

Weight

- 259 Lbs. assembled
- 419 Lbs. shipping weight

Doors

- 6, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- 26 top louvers – In top cover, under Alumishield™
- One removable filter panel per door
- 26 fixed filter pads in top cover

Handles

- Stainless steel, padlocking

Lifting Hooks

- 4, standard

Racking Specifications

Rails

- Three sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .160" Material (Alumiflex™)

Spacing

- 19" or 23" Racking available

Useable Height

- 26.25"

Useable Depth

- Maximum: 21.5" Minimum: 19.75"

Inside Clearance - Less Rails

Height

- 30"

Width

- 27.625" each compartment

Depth

- See racking specifications
- Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 26.75"

Width

- 23.625"

Exterior Cabinet Dimensions

Main Body

- Height: 30.98"
- Width: 88.5"
- Depth: 25"

Alumishield™

- Hang down height: 1.75"
- Width: 93.5"
- Depth: 29.5"

Handles

- Protrude 1.875"

Total Space Occupied

- Height: 31.605"
- Width: 94.5"
- Depth: 28.75"

| | *Section Starting & Ending Points | Vertical Height Per section | Effective Depth For Each Section |
|--------|-----------------------------------|-----------------------------|----------------------------------|
| Top | 26.75" – 30.98" | 3.25" | 21.50" |
| | 26.57" – 26.75" | .18" | 20.50" |
| | 21.00" – 26.57" | 5.57" | 21.50" |
| Center | 9.00" – 21.00" | 12.00" | 19.75" |
| | 3.43" – 9.00" | 5.57" | 21.50" |
| | 3.25" – 3.43" | .18" | 20.50" |
| Bottom | 0.00" – 3.25" | 3.25" | 21.50" |