

30D-62DDXC-POP3-4

78" H x 88.5" W x 42" D (99 RU*) Outdoor Enclosure



General

Weight

- 620 Lbs. assembled
- 780 Lbs. shipping weight

Doors

- 6, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- 26 top louvers – In top cover, under Alumishield®
- One removable filter panel per door
- 26 fixed filter pads in top cover

Handles

- Stainless steel, padlocking

Lifting Hooks

- 8, standard

Racking Specifications

Rails

- Six sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .160" Material (Alumiflex®)

Spacing

- 19" or 23" Racking available

Useable Height

- 57.75"

Useable Depth

- Maximum: 38.5" Minimum: 36.75"

Inside Clearance - Less Rails

Height

- 62"

Width

- 27.625" each compartment

Depth

- See racking specifications
- Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 58.25"

Width

- 23.625"

Exterior Cabinet Dimensions

Main Body

- Width: 88.5"
- Height: 62.23"
- Depth: 42"

Alumishield®

- Hang down height: 1.75"
- Width: 93.5"
- Depth: 45.5"

Handles

- Protrude 1.875"

Total Space Occupied

- Total Height: 78.96"
- Cabinet Height: 63.105"
- Battery Box: 17.605"
- Width: 110"
- Depth: 42"

* Front and Rear sets of rails allow some equipment to rack both directions providing up to 198 RU

POP3-4 Enclosures Come With:

- LC-200 200 Amp Main Load Center w/ (6) 4-Square Outlets, (2) 220V Outlets
- 3 Fluorescent Lights
- Lifting Hooks
- Door Windlocks
- Door Alarms
- 4" C-Channel Feet for Mounting
- 2 - 8000 BTU Air Conditioner 220 Volts with 800 Watts Total Fan Heaters (16K Total BTU)
- Spool-Up Side Box – 26"H X 22"W X 10"D
- Battery Boxes - 3 Separate Battery Compartment Tray's for a 30D

| | *Section Starting & Ending Points | Vertical Height Per section | Effective Depth For Each Section |
|--------|-----------------------------------|-----------------------------|----------------------------------|
| Top | 58.75" – 62.48" | 3.25" | 38.50" |
| | 58.57" – 58.75" | .18" | 37.50" |
| | 37.00" – 58.57" | 21.57" | 38.50" |
| Center | 25.00" – 37.00" | 12.00" | 36.75" |
| | 3.43" – 25.00" | 21.57" | 38.50" |
| | 3.25" – 3.43" | .18" | 37.50" |
| Bottom | 0.00" – 3.25" | 3.25" | 38.50" |