

OD-62DDXC

62" H x 42" D (33 RU*) Outdoor Enclosure



General

Weight

- 210 Lbs. assembled
- 255 Lbs. shipping weight

Doors

- 2, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- 12 top louvers – In top cover, under Alumishield®
- One removable filter panel per door
- 12 fixed filter pads in top cover

Handles

- Stainless steel, padlocking

Racking Specifications

Rails

- Two set standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex®)

Spacing

- 19" or 23" Racking available

Useable Height

- Usable racking height has been revised to only fit in the opening of the door jam which is cabinet height minus 4.25"
- Maximum: 58.25"
- Number of rack units per rail set: 33
- Total number RU's: Up to 66*

Useable Depth

- Maximum: 38.5" Minimum: 28.75"

Inside Clearance - Less Rails

Height

- 62.23"

Width

- 23.625"

Depth

- See racking specifications
- Useable depth

Ratings

NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 58.25"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 62.48"
- Width: 25.5"
- Depth: 42"

Alumishield®

- Hang down height: 1.75"
- Width: 28.46"
- Depth: 44.669"

Handles

- Protrude 1.875"

Total Space Occupied

- Height: 63.105"
- Width: 28.46"
- Depth: 45.75"

* Front and Rear sets of rails allow some equipment to rack both directions providing up to 66 RU

| | *Section Starting & Ending Points | Vertical Height Per section | Effective Depth For Each Section |
|--------|-----------------------------------|-----------------------------|----------------------------------|
| Top | 58.75" – 62.48" | 3.25" | 38.50" |
| | 58.57" – 58.75" | .18" | 37.50" |
| | 37.00" – 58.57" | 21.57" | 38.50" |
| Center | 25.00" – 37.00" | 12.00" | 36.75" |
| | 3.43" – 25.00" | 21.57" | 38.50" |
| | 3.25" – 3.43" | .18" | 37.50" |
| Bottom | 0.00" – 3.25" | 3.25" | 38.50" |