

OOD-30DXC-B1

46" H x 25" D (15 RU) Outdoor Enclosure



General

Weight

- 150 Lbs. assembled
- 230 Lbs. shipping weight

Doors

- Four – secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

BOD-DX

- Battery Box enclosure with slide out battery tray

Handles

- Stainless steel, padlocking

Racking Specifications

Rails

- 2 standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" EIA standard

Useable Height

- Height: 30" (Top Enclosure)

Useable Depth

- Maximum: 21.5" Minimum: 19.75"

Inside Clearance - Less Rails

Height

- 30"

Width

- 23.625" each side

Depth

- See racking specifications – Useable depth

Ratings

NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c), NEMA 4X

Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

Door Opening Clearance

Height

- 25.8125"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 47"
- Width: 25.5"
- Depth: 25"

Alumishield™

- Hang down height: 1.75"
- Width: 28"
- Depth: 27.625"

Handles

- Protrude 1.875"

Total Space Occupied

- Height: 47.5"
- Width: 28"
- Depth: 29"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	26.75" – 30.00"	3.25"	21.50"
	26.57" – 26.75"	.18"	20.50"
	21.00" – 26.57"	5.57"	21.50"
Center	9.00" – 21.00"	12.00"	19.75"
	3.43" – 9.00"	5.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"