

# OOD-30DXC-B1AC1

## 46" H x 25" D (15 RU) Outdoor Enclosure



### General

#### Weight

- 220 Lbs. assembled
- 270 Lbs. shipping weight

#### Doors

- Four – secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

#### Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

#### BAC

Configuration comes with the following:

- 2400 BTU Air conditioner 110 Volts (Internal Heat option)
- With / R3.3 Insulation,
- Battery Box enclosure with slide out battery tray

#### Handles

- Stainless steel, padlocking

### Racking Specifications

#### Rails

- 2 standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

#### Spacing

- 19" EIA standard

#### Useable Height

- Height: 30" (Top Enclosure)

#### Useable Depth

- Maximum: 21.5" Minimum: 19.75"

### Inside Clearance - Less Rails

#### Height

- 30"

#### Width

- 23.625" each side

#### Depth

- See racking specifications – Useable depth

### Ratings

#### NEMA Class Types available

- NEMA 4X

#### Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

### Door Opening Clearance

#### Height

- 25.8125"

#### Width

- 19.5"

### Exterior Cabinet Dimensions

#### Main Body

- Height: 47"
- Width: 25.5"
- Depth: 25"

#### Alumishield™

- Hang down height: 1.75"
- Width: 28"
- Depth: 27.625"

#### Handles

- Protrude 1.875"

#### Total Space Occupied

- Height: 47.5"
- Width: 28"
- Depth: 29"

### Comes with:

- Bottom Battery Compartment
- 2400 BTU Air Conditioner 110 Volts
- .5 Insulation
- Populated 4 Square Outlet

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	26.75" – 30.00"	3.25"	21.50"
	26.57" – 26.75"	.18"	20.50"
	21.00" – 26.57"	5.57"	21.50"
Center	9.00" – 21.00"	12.00"	19.75"
	3.43" – 9.00"	5.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"