

R7-54DXCW-ACD

54" H x 25" D Wimax-LTE (29 RU) Outdoor Enclosure

18



Air Conditioner

Size

- 4000 BTU

Voltage

- 220 Volts AC

Dimensions

- 30.1" H x 12.27" W x 8.34" D

Security

- Programmable

Constructed

- Durable 16 gauge welded steel construction

NEMA

- Optional 4, 4X class & divisional

General

Weight

- 270 Lbs. assembled
- 305 Lbs. shipping weight

Doors

- 2, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex™
- Finish: Flat aluminum
- RF properties: Non-ferrous

Handles

- Stainless steel, padlocking

Racking Specifications

Rails

- 2 standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" or 23" Racking available

Useable Height

- Height: 54"

Useable Depth

- Maximum: 21.5" Minimum: 19.75"

Spool Up Side Box

Dimensions

- 26" H x 22" W x 10" D

Security

- 2 Quarter turns Screwdriver Lock

Constructed

- Out of .125" Alumiflex™ Continuously welded on all seams

Finish

- Polished, unpainted aluminum

NEMA

- Weatherproof aluminum filled gasket seals top lid

Plate

- .75" plywood removable plate

Ground Bar

- .25" x 2" x 10"; 10 pairs 7/16" holes

Inside Clearance - Less Rails

Height

- 54"

Width

- 23.625"

Depth

- See racking specifications
- Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 4X

Door Opening Clearance

Height

- 49.875"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 54.25"
- Width: 25.5"
- Depth: 25"

Alumishield™

- Hang down height: 1.75"
- Width: 28.46"
- Depth: 27.67"

Handles

- Protrude 1.875"

Total Space Occupied

- Height: 54.75"
- Width: 38.25"
- Depth: 35.25"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	46.75" – 54.00"	3.25"	21.50"
	46.57" – 46.75"	.18"	20.50"
	31.00" – 46.57"	15.57"	21.50"
Center	19.00" – 31.00"	12.00"	19.75"
	3.43" – 19.00"	15.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"