

R7-62DDCW-ACD

62" H x 34" D (51 RU) Outdoor Enclosure



Air Conditioner

Size

- 6000 BTU

Voltage

- 220 Volts AC

Dimensions

- 35.97" H x 15.94" W x 7.35" D

Security

- Programmable

Constructed

- Durable 16 gauge welded steel construction

NEMA

- Optional 4, 4X class & divisional

General

Weight

- 315 Lbs. assembled
- 375 Lbs. shipping weight

Doors

- 2, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

Material

- .125" Alumiflex™
- Finish: Flat aluminum
- RF properties: Non-ferrous

Handles

- Stainless steel, padlocking

Racking Specifications

Rails

- 4 standard, 2 half length (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" or 23" Racking available

Useable Height

- Height: 62"

Useable Depth

- Maximum: 30.5" Minimum: 28.75"

Spool Up Side Box

Dimensions

- 26" H x 22" W x 10" D

Security

- 2 Quarter turns Screwdriver Lock

Constructed

- Out of .125" Alumiflex™ Continuously welded on all seams

Finish

- Polished, unpainted aluminum

Plate

- .5" plywood removable plate

NEMA

- Weatherproof aluminum filled gasket seals top lid

Inside Clearance - Less Rails

Height

- 62"

Width

- 23.625"

Depth

- See racking specifications
- Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 57.875"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 62.25"
- Width: 25.5"
- Depth: 34"

Alumishield™

- Hang down height: 1.75"
- Width: 28.46"
- Depth: 38.6875"

Handles

- Protrude 1.875"

Total Space Occupied

- Height: 62.875"
- Width: 38.25"
- Depth: 44.25"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	58.75" – 62.00"	3.25"	30.50"
	58.57" – 58.75"	.18"	29.50"
	37.00" – 58.57"	21.57"	30.50"
Center	25.00" – 37.00"	12.00"	28.75"
	3.43" – 25.00"	21.57"	30.50"
	3.25" – 3.43"	.18"	29.50"
Bottom	0.00" – 3.25"	3.25"	30.50"