

ST-30DD

30" H x 34" D (33 RU) Indoor Enclosure



General

Weight

- 69 Lbs.

Doors

- 2, secured with non-intrusion locks
- Locks and unlocks with supplied set of keys
- Designed to mount, either left or right

Material

- .1" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 2 – 8" X 10" standard filter panel housings
- One removable filter panel per door
- Solid panels can be used for non-ventilation

Access Holes

- 4 – 1" hole with hole plug installed

Racking Specifications

Rails

- Four standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" EIA standard

Useable Height

- 30"

Useable Depth

- Maximum: 33.6875"
- Minimum: 31.9375"

Inside Clearance - Less Rails

Height

- 30"

Width

- 21"

Depth

- See racking specifications – Useable depth

Ratings

NEMA Class Types available

- Class 250 Type 2

Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

Door Opening Clearance

Height

- 26.75"

Width

- 19.5"

Exterior Cabinet Dimensions

Main Body

- Height: 30.25"
- Width: 23.25"
- Depth: 34.25"

Screws

- Protrude .1875" on each side

Total Space Occupied

- Height: 30.25"
- Width: 23.625"
- Depth: 34.375"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	28.32" – 30.00"	1.68"	31 15/16"
	19.00" – 28.32"	9.32"	33 11/16"
Center	11.00" – 19.00"	8.00"	33 3/16"
	1.68" – 11.00"	9.32"	33 11/16"
Bottom	0.00" – 1.68"	1.68"	14 15/16"