

# ST-30DX

## 30" H x 25" D (17 RU) Indoor Enclosure



### General

#### Weight

- 53 Lbs.

#### Doors

- 2, secured with non-intrusion locks
- Locks and unlocks with supplied set of keys
- Designed to mount, either left or right

#### Material

- .1" Alumiflex™

- Finish: Painted cream
- RF properties: Non-ferrous

#### Vents

- 2 – 8" x 10" standard filter panel housings
- One removable filter panel per door
- Solid panels can be used for non-ventilation

#### Access Holes

- 4 – 1" hole with hole plug installed

### Racking Specifications

#### Rails

- Two standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

#### Spacing

- 19" EIA standard

#### Useable Height

- 30"

#### Useable Depth

- Maximum: 24.6875"
- Minimum: 22.9375"

### Inside Clearance - Less Rails

#### Height

- 30"

#### Width

- 21"

#### Depth

- See racking specifications – Useable depth

### Ratings

#### NEMA Class Types available

- Class 250 Type 2

#### Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

### Door Opening Clearance

#### Height

- 26.75"

#### Width

- 19.5"

### Exterior Cabinet Dimensions

#### Main Body

- Height: 30.25"
- Width: 23.25"
- Depth: 25.25"

#### Screws

- Protrude .1875" on each side

#### Total Space Occupied

- Width: 23.625"
- Height: 30.25"
- Depth: 25.375"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	28.32" – 30.00"	1.68"	22 15/16"
	19.00" – 28.32"	9.32"	24 11/16"
Center	11.00" – 19.00"	8.00"	24 3/16"
	1.68" – 11.00"	9.32"	24 11/16"
Bottom	0.00" – 1.68"	1.68"	22 15/16"