

SY-32DXL

32" H x 23" W x 25" D (18 RU) Indoor Enclosure





General

Weight

- 90 Lbs. assembled
- 145 Lbs. shipping weight

Doors

- Front door has framed see thru
 .25 " Lexan
- Rear door is Alumiflex[™] construction, both doors have lift off hinges
- 5 " plenum below rear door has removable access plates for cable entries

Handles

• 2 - 5" spring loaded handles one on each side of cabinet.

Racking Specifications

Rails

- Two sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

• 19" EIA standard

Useable Depth

- Maximum: 21.5"
- Minimum: 19.75"

Ratings

NEMA Class Types available

Class 250 Type 2

Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

Inside Clearance - Less Rails

- Height: 32"
- Width: 23"
- Depth: 25

Exterior Cabinet Dimensions

Main Body

- Height: 32.25"
- Width: 23.25"
- Depth: 25.25"

Screws

· Protrude .1875" on each side

Total Space Occupied

- Height: 32.25"
- Width: 23.625"
- Depth: 25.375"

Comes standard with:

- 2 Perforated Mounting Shelf's
- 110V Fan Kit w/ Thermostat