

SY-50DXL

50" H x 23" W x 25" D (28 RU) Indoor Enclosure



General

Weight

- 105 Lbs. assembled
- 155 Lbs. shipping weight

Doors

- Front door has framed see thru .25" Lexan
- Rear door is Alumiflex™ construction, both doors have lift off hinges
- 5" plenum below rear door has removable access plates for cable entries

Handles

- 2 - 5" spring loaded handles one on each side of cabinet

Racking Specifications

Rails

- Two sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" EIA standard

Useable Depth

- Maximum: 21.5"
- Minimum: 19.75"

Comes standard with:

- 2 - Perforated Mounting Shelf's
- 110V Fan Kit w/ Thermostat

Ratings

NEMA Class Types available

- Class 250 Type 2

Paint Tested

- 1000 Hour salt spray
- 1000 Hour immersion

Inside Clearance - Less Rails

- Height: 50"
- Width: 23"
- Depth: 25"

Exterior Cabinet Dimensions

Main Body

- Width: 23"
- Height: 50"
- Depth: 25"

Total Space Occupied

- Height: 50.25"
- Width: 23.625"
- Depth: 25.625"

Screws

- Protrude .1875" on each side