

WLTEE1-A

67" H x 30" W x 34" D (27 RU) (AC Unit Version) Wimax & LTE
(Wide w/Single Battery Compartment)

18



General - Outdoor Enclosure with Front and Rear Door

Total Occupied Space

- Height: 67.78"
- Width: 40"
- Depth: 46"

Top Compartment:

- Height: 47.38"
- Height: Racking Rails 48.16"
- Rails tapped for 10-32 screws, (2) pass through holes per rail
- Front and Rear sets of Adjustable 19" or 23" racking.
- Total Racking Units: 27

Bottom Compartment:

- Height: 14.26" (two compartments each 12.82")
- Depth: Maximum: 30.5" Minimum: 28.75"

Spool-Up Side Box

- Height 32 3/16"H
- Wide 26"W
- Deep 10"D
- Removable plywood back-plate
- 5 - 2" cable pass through openings;
- 4 for the primary compartment
- 1 for the battery cables.



Features

- Heavy Duty Lifting Hooks.
- Baked on White Textured Powder Coat Paint.
- 12" Copper ground bar on 14"risers with isolators.

Electrical

- Dual panel AC load center with 50 amp back-up generator plug. Interior convenience outlets and 220V supplied junction box for DC power system.

Cooling

- Air Conditioned Top Compartment (NEMA 4)
- 6000 BTU Air Conditioner, 220V programmable with 400 watts of heat
- Fan cooled Battery Compartment (NEMA 3R) using (2) 5", 48V, 110CFM fans and thermostat.
- HT-300 300 Watt Heater Strip