

20D-62DXC

(132 RU) Outdoor Enclosure



Picture shown are examples only : See details for specifications



General

*Approximate Weight

- 380 Lbs. assembled
- 530 Lbs. shipping weight

Doors

- 4, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with 3/8" aluminum filled gaskets
- 4 Auto door stops standard

Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- 20 top louvers – In top cover-under Alumishield™
- One removable filter panel per door
- 20 fixed bug screens in top cover

Handles

- Zind Die Powder-coated Black EMKA Three Point Padlocking Handles

Lifting Hooks

- 4, standard

Racking Specifications

Rails

- Four sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" or 23" Racking available

Inside Clearance - Less Rails

Height

- 62.23"

Width

- 27.625" each side

Depth

- 18.75"

Ratings

NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c), NEMA 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 58.25"

Width

- 23.5"

Exterior Cabinet Dimensions

Main Body

- Height: 62.48"
- Width: 59"
- Depth: 25"

Alumishield™

- Hang down height: 1.71"
- Width: 61.96"
- Depth: 27.67"

Handles

- Protrude 2.2"

Total Space Occupied

- Height: 63.105"
- Width: 65"
- Depth: 29.4"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	58.75" – 62.48"	3.25"	21.50"
	58.57" – 58.75"	.18"	20.50"
	37.00" – 58.57"	21.57"	21.50"
Center	19.00"-31.00"	12.00"	19.75"
	3.43" – 25.00"	21.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"