

# WOD-50DDC

50.23" H 29.5" W x 25" D (26 RU) Outdoor Enclosure



## General

### \*Approximate Weight

- 173 Lbs. assembled
- 243 Lbs. shipping weight

### Doors

- 2, Secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .375" bulb gaskets
- EMKA Wind Lock on Each Door

### Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

### Vents

- 30 bottom louvers per door
- 16 top louvers – In top cover, under Alumishield®
- One removable filter panel per door
- 16 fixed filter pads in top cover

### Handles

- Zinc Die Powder-coated Black EMKA Three Point Padlocking Handles

### Exterior Screws

- Stainless steel with sealing washers & nylon locking nuts

## Racking Specifications

### Rails

- 2 Sets of 19" or 23" Reversible Racking Rails w/RU Markings and Pass-through Holes
- Alodine coated
- Holes tapped for 10 x 32 threads
- Each rail supported by three R-STRUTS™
- .125" (Alumiflex®)

### Rail Pass-Throughs

- Each rail has 2 pass-through holes with grommets. Holes are 1.75 diameter

### Spacing

- 19" - 23" Racking standard

### Positioning

- All rails fully adjustable from front to rear

## Inside Clearance - Less Rails

- Height: 49.98"
- Width: 27.625"
- Depth: 27.75"

## Ratings

### NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

### Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

## Door Opening Clearance

- Height: 46"
- Width: 23.5"

## Exterior Cabinet Dimensions

### Main Body

- Height: 50.23"
- Width: 29.5"
- Depth: 34"

### Alumishield®

- Hang down height: 1.71"
- Width: 32.46"
- Depth: 36.67"

### Handles

- Protrude 2.2"

### Total Space Occupied

- Height: 50.855"
- Width: 32.46"
- Depth: 38.4"

Pictures shown are examples only.  
See details for specifications.