

# OD Series OD-62DDC



## Why Choose the OD Series?

The OD series of enclosures are the ultimate choice for your outdoor racking requirements. Being made of our own rugged Alumiflex®, you'll find it noticeably lighter than steel, yet strong enough to rack even the heaviest equipment. When choosing the OD series, you have handpicked the highest value in American construction. The OD-62DDC includes the standard features you have come to expect with DDB, incorporating the versatile rail strut (R-Strut) system for adjustable racking, the security of a 3-point locking system and our patented Alumishield® solar cap to manage heat loads. For those who need more than just our standard enclosure, DDB can also make a truly customized solution with our many available options including HVAC, providing a climate-controlled environment for any electronic equipment, electrical load panels and cable entry solutions to name a few. All of this comes together to create an enclosure able to meet all of the unique needs your customers have been seeking. DDB offers a state-of-the-art design, a competitive price, benchmark lead times and a guaranteed delivery, all backed up with an industry leading 15-year warranty on every enclosure. Put DDB's substantial stock to work for you today. Contact our professional staff to assist you with your made-to-order solution.

Application Types Telecommunications Wireless/Broadband Fiber Optics Back Haul Small Cell/DAS Public Safety Utility Base Station Military Trailer-Based Communications Wi-Fi LTEE/4G/5G

2301 S. HWY 77 Pauls Valley, OK 73075 T: (800) 753-8459 – F: (877) 220-7236



#### Environmental & Safety Ratings:

- ✓ NEMA 3R, IP 24 (shown above)
- ✓ NEMA 4 and 4X, IP 66 configurable (not shown)
- ✓ OD-62 Series, ETL environmentally listed to UL 50/50E, Type 4's Available here: <u>https://www.ddbunlimited.com/new-ul-50e-listed/</u>
- ✓ ETL listed; Safety Requirements, UL 62368-1:2019 Ed.3, CSA C22.2



#### Features

0.125" Aluminum Construction Stainless Steel External Hardware/Hinge 3 Point Lock System Heavy Duty Out-Door Construction Front and Rear Access Custom Colors Available Cream Powder-Coat in Stock Flexible and Scalable 15 Year Warranty Quick Shipping

### Weight and Dimensions

Approximate Exterior Enclosure Dimensions: 63"H x 28"W x 39"D Shipping Dimensions: 32"W x 42"L- Palletized Approximate Shipping Weight: 207 lbs.

sales@ddbunlimited.com www.ddbunlimited.com

## OD Series OD-62DDC





#### Features

- 1. Alumishield
- Front and Rear 19" Adjustable Racking Rails, 66 RU's
- 3. Rear Access Door

II (R)

ISO 9001 & 27001

Certified company

- 4. Stainless Steel Door Hinge
- 5. 3 Point Locking System
- 6. Powder-Coat Cream
- 7. Reusable Vent Filters

2301 S. HWY 77 Pauls Valley, OK 73075 T: (800) 753-8459 – F: (877) 220-7236 sales@ddbunlimited.com www.ddbunlimited.com Intertek

Installation, operating and safety instructions can be downloaded here



Scan this code for replacement parts



Rev C





