

OD-UL Series OD-16DXC-UL50



Why Choose the OD-UL Series?

The OD-UL series of enclosures are the ultimate choice for your outdoor racking requirements. Being made of our own rugged Alumiflex®, you'll find it noticeably lighter than steel, yet strong enough to rack even the heaviest equipment. When choosing the OD-UL series, you have handpicked the highest value in American construction. The OD-UL series includes the standard features you have come to expect with DDB, incorporating the versatile strut system for adjustable racking, the security of a 3- point locking system, our patented Alumishield® solar cap to manage heat loads, UL listed grounding straps, & UL listed gasketing. For those who need more than just our standard enclosure, DDB can also make a truly customized solution with our many available options including HVAC, providing a climate-controlled environment for any electronic equipment, electrical load panels and cable entry solutions to name a few. All of this comes together to create an enclosure able to meet all of the unique needs your customers have been seeking. DDB offers a state-of-the-art design, a competitive price, benchmark lead times and a guaranteed delivery, all backed up with an industry leading 15-year warranty on every enclosure. Put DDB's substantial stock to work for you today. Contact our professional staff to assist you with your made-to-order solution.

Application Types

Telecommunications Wireless/Broadband Fiber Optics Back Haul Small Cell/DAS Public Safety Utility Base Station Military Trailer-Based Communications Wi-Fi LTEE/4G/5G



Environmental & Safety Ratings:

- ✓ ETL environmentally listed to UL 50/50E, IP 66, Type 4
- ✓ ETL listed; Safety Requirements, UL 62368-1:2019 Ed.3, CSA C22.2





Features

0.125" Aluminum Construction Stainless Steel External Hardware/Hinge Fully Welded Construction 3 Point Lock System Front and Rear Access Custom Colors Available Cream Powder-Coat in Stock Flexible and Scalable 15 Year Warranty Quick Shipping Water/Rain/Sleet/Dust Tight

Weight and Dimensions

Approximate Exterior Enclosure Dimensions: 18"H x 28"W x 30"D Shipping Dimensions: 35"W x 42"L - Palletized

Approximate Shipping Weight:

T: (800) 753-8459 – F: (877) 220-7236 sales@ddbunlimited.com www.ddbunlimited.com


2301 S. HWY 77 Pauls Valley, OK 73075

95 lbs.



OD-UL Series OD-16DXC-UL50





Features

- 1. Alumishield
- 2. 19", Adjustable, Racking Rails, 7 RU's
- 3. Rear Access Door
- 4. 3 Point Locking System
- 5. Ground Strap UL Listed
- 6. Frame Gasket UL Listed

2301 S. HWY 77 Pauls Valley, OK 73075 T: (800) 753-8459 – F: (877) 220-7236 sales@ddbunlimited.com www.ddbunlimited.com





Installation, operating and safety instructions can be downloaded here




Scan this code for replacement parts









File Location: (DDB)(EPDM Vault:) C:\DDB\Drawing Requests\Customers\DDB WEB DWG\OD Family-UL50 WEB\OD-16DX-UL50
