

UL-50 WOD SERIES





Why Choose the WOD-UL Series?

The WOD-78DXC-UL50 enclosure is the pinnacle of enclosures. With a fully welded chassis, heavy duty vulcanized gasketing and years of design and engineering behind it, you will find this will meet the most stringent requirements of the UL-50E Type 4 listing. Fully tested by a third party Nationally Recognized Testing Laboratory and listed to the UL-50E standard, you can trust that the WOD UL series will pass any test or inspection it faces. Designed with public safety requirements in mind, these units can be place in mission critical locations where communication or sensitive gear needs to be protected regardless of the situation. As with the standard WOD series, the WOD-UL series comes with standard 3-point locking, front and rear access with integrated wind locks, top mounted solar shield, adjustable R-strut racking, reversible 19" or 23" EIA racking, Alumiflex construction and our unmatched 15-year warranty. Moreover, there is an extensive list of optional accessories including HVAC units, electrical panels, and cable entry solutions to name a few. No matter the application, DDB provides cutting-edge design, competitive pricing, benchmark lead times, and guaranteed delivery. Whether you require a custom enclosure or something from our substantial stock, our professional staff is here to help you today.

Application Types

Telecommunications
Wireless/Broadband
Fiber Optics
Back Haul
Public Safety
DAS
Utility
Base Station
Military
Trailer-Based Communications
Wi-Fi

2301 S. HWY 77 Pauls Valley, OK 73075 T: (405)-665-2876

LTEE/4G/5G



Environmental & Safety Ratings:

✓ ETL environmentally listed to UL 50/50E, IP 66, Type 4

✓ ETL listed; Safety Requirements, UL 62368-1:2019 Ed.3, CSA C22.2



Features

15 Year Warranty

0.125" Aluminum Construction

3-Point Locking System

Heavy Duty Out-Door Construction

Front and Rear Access

Stainless Steel External Hardware/Hinge

Cream Powder-Coat, Standard

Wind Locks

Quick Shipping

Weight and Dimensions

Approximate Exterior Enclosure Dimensions:

79"H x 33"W x 30"D

Shipping Dimensions:

42"L x 32"W x 84"H- Palletized

Approximate Shipping Weight:

250 lbs.



UL-50 WOD SERIES

WOD-78DXC-UL50





- 1. Alumishield
- Wind Locks
- 3. 19" and 23" Adjustable Racking Rails
- 4. Stainless Steel Door Hinge
- 5. 3-Point Locking System
- 6. Heavy Duty 0.160" Doors
- 7. Powder-Coat Cream
- 8. Rear Door Access



Climate Control

Scan this code for



Scan this code for Accessories



T: (405)-665-2876 sales@ddbunlimited.com www.ddbunlimited.com





